

WEATHERPROOF TELEPHONE

HNEX105-FK-SIP



Description:

HNEX105-FK-SIP Weatherproof Telephones are fully contained within a corrosion resistant cast aluminium weatherproof case with a door providing complete protection against dust and moisture ingress, resulting in a highly reliable product with a long MTBF. The unique robust handset is manufactured from moulded bulk molding compound and designed specifically to withstand arduous use in all environments, armoured cord to provide additional resistance to vandalism or heavy industrial use.

HNEX105-FK-SIP Weatherproof Telephones are designed for use by the railways, power stations, the armed services and heavy industry which require very reliable telephony under adverse conditions.

Features:

- Standard SIP phone with LCD display
- Vandal resistant handset and cord
- Weather proof protection to IP66
- Waterproof full keypad
- "LR" button for last number redial
- "R" for flash recall
- "M" for muting
- Wall mounting, Easy for installation
- PoE or external power supply (SIP-VoIP)
- RJ45 port for SIP phone

WEATHERPROOF TELEPHONE

Voice Features:

- Support SIP 2.0 (RFC3261)
- Codec: G.711A/u, G.7231 high/low, G.729, G.722
- Echo cancellation: Support G.168 and hand-free can support 96ms
- Supports full duplex
- SIP support SIP domain, SIP authentication(none, basic,MD5),DNS name of server
- DTMF: SIP info, DTMF relay, RFC2833
- Call control features: Flexible dial map, support hot-line

Network Features:


- WAN/LAN: support bridge mode
- Support static IP address
- Support DHCP get IP on WAN port
- Support VLAN
- Support web config

Specification:

Model	HNEX105-FK-SIP
Power Input	12-24V DC PoE: IEEE802.3af (optional)
Port	WAN: 10/100Base- T RJ-45 for LAN, Auto MDIX LAN: 10/100Base- T RJ-45 for PC, Auto MDIX
Power Consumption	Idle:1.5W/ active:1.8W
Casing Material	Die cast aluminium back cover and stainless steel face plate, Epoxy powder coated.
Colors	Yellow, other colors to special order
Handset Material	Durable ABS plastic with stainless steel spiral cord
Keypad	Rubber keypad
Temperature	Operating: -30°C to +70°C Storing: -40°C to +75°C
Weather Resistance	IP66
Ringtone	Shrill warble tone 90dBA @ 1 metre typical
Hook Switch	Electronic / magnetic with no visible moving parts
M.T.B.F.T	Calculated to have an M.T.B.F. in excess of 60,000 hours using
Weight	Up to 6 kg depending on option

WEATHERPROOF TELEPHONE

Dimensions:



(Measured in MM)

Package:

unit size: 204 * 334 * 109(mm)

Carton size: 200 * 300 * 440(mm)

Packaging materials: pearl cotton, carton

Gross weight: 6KG Net weight: 5KG

Approvals:



This mark indicates compliance with the:
Radio & Telecommunications Terminal Equipment
Directive
2004/108/EC



This mark indicates compliance with the:
FCC Part 15 Subpart B Class B