



MAIN UNIT:

- ✓ Power consumption of main unit :450W
- ✓ Each unit can support 60 units' delegate and chairman microphone, it could be extended to support 200 units' microphone by adding more Extension power supply unit.
- ✓ With four group 8-DIN socket for multi-line connection
- ✓ With one group wired microphone input port, independent volume adjusted
- ✓ High fidelity sound quality
- ✓ With audio input signal and REC output
- ✓ Built-in 1W monitor loudspeaker volume adjusted
- ✓ System volume independent adjusted
- ✓ RCA input. For telephone coincidence
- ✓ XLR output; Mix output two group—TRS, RCA
- ✓ Special "T" type single cable with DIN socket
- ✓ 220V/50Hz
- ✓ N.G: 5.15kg
- ✓ External dimensions :485mm (includes microphone pipe) ×100mm (2U, includes engine case foot pad) ×355mm (W×H×D); It can be put on the table or install in the 19inch standard frame.

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice

Conference System

MC350A DC350B



CHAIRMAN UNIT (MC350A)

- ✓ Frequency response: 40-16000Hz
- ✓ Sensitivity: -42dB±2dB
- ✓ Speaking reference distance: 20-120cm
- ✓ Built-in 1W 8Ω loudspeaker
- ✓ The indicative lamp will on when open the microphone
- ✓ Microphone was supplied power by main unit
- ✓ Has TALK button and indicative lamp, it can control speaking status freely.
- ✓ Has automatic closed function: Microphone will off after speech in 45 seconds
- ✓ Use connection cables of SYSTEM B type. Has 8P-DIN socket for "T" type connection of system, the extension cables can be ordered according to the real situation of the conference hall.
- ✓ Chairman Unit has priority button which can cut the signal of the delegate units, so that it can control the order for conference.

DELEGATE UNIT (DC350A)

- ✓ Frequency response: 40-16000Hz
- ✓ Sensitivity: -42dB±2dB
- ✓ Speaking reference distance 20-120cm
- ✓ Built-in 1W 8Ω loudspeaker
- ✓ The indicative lamp will on when open the microphone
- ✓ Microphone was supplied power by main unit
- ✓ Has TALK button and indicative lamp, it can control speaking status freely.
- ✓ Has automatic closed function: Microphone will off after speech in 45 seconds
- ✓ Use connection cables of SYSTEM B type. Has 8P-DIN socket for "T" type connection of system, the extension cables can be ordered according to the real situation of the conference hall.

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice