

8 Channel Mixer With DSP

CMD8



FEATURE:

- 2 optional DSP effective modules, one is 21 effective model, can adjust the time. The other has adjustable and fixed parameter.
- Intelligent display, accurate, convenient.
- + 48V phantom power.
- SMT.
- Built in 24-bit DSP effector.
- 3 balanced input, double 7 balanced output.
- 2 main output, 1 monitor output, 1 effect sending.
- Led DJ light.

SPECIFICATION:

Model	CMD8
Mono Input Channel	8 channel
Stereo Input Channel	2 channels(selectable.if selected, mono channels will be lessened 4 channels)
Mono Insart Channel	8 channel
Phantom power for MIC	+48V
Output Channel	2 Main Output channels; 2REC output channels; 1 effects output channels; 1 monitor output channels; 1 streophone output channel
Frequency Response	20Hz ~20KHZ $\pm$ 1dB
Mono MIC to Main Output Max Gain	50dB $\pm$ 3dB
Mono Line to Main Output Max Gain	30dB $\pm$ 3dB
Stereo Line to Maain Output Max Gain	N.A.
Overhearing	80dB $\pm$ 1.5dB @ 1kHz
S/NR	78dB @ 0dB
Max Output leval to main output channel	22dB $\pm$ 1.5dB
Max unbalance Group Output/Main Output Channel	16dB $\pm$ 1.5dB, without Group
REC max unbalanced output	16dB $\pm$ 1.5dB
Monitor max unbalance Output	16dB $\pm$ 1.5dB
Effects Max Unbalance Output	16dB $\pm$ 1.5dB
Phone Output	12dB $\pm$ 1.5dB @ 1KHz 32 Ω
Gain Inequality	2dB
THD	0.02% @ 0dB 1 KHz
Mono Channel EQ	
High Mid/Low	12KHz, 1.8KHz, 80Hz
Frequency Swing&Gain	Frequency swing<8%;Gain: 15dB
Stereo EQ	
High Mid/Low	12KHz, 1.8KHz, 80Hz
Frequency Swing & Gain	Frequency swing<8%;Gain: 15dB
7 Main Output to GEQ	
Center Frequency of EQ	63Hz, 16Hz, 400Hz, 1KHz, 6.3KHz, 16KHz
Frequency Swing & Gain	$\pm$ 12dB inaccruracy 2 dB, Frequency swing<8%
Effector	2 DSP of 21 defferent Effects: HALL,ROOM,PLATE,AMBINENT,GATED,REVERS,VOICE,DEL & REV,ECHO 40,ECHO 50,DELAY,CHORUS,CHO & DEL,CHO & REV, FLANGER,FLA & DEL FLA,FLA & REV, TREMOLLO,TRE&REV,WAHWAH,WAH&REV
Clipping Indicator Light	Indicator 3 dB earlier than cutting wave level
Group & 12 Main Outputs Levels Indicator LED	+9dB,+6dB,+3dB,0dB,-2dB,-4dB,-6dB,-9dB,-12dB,-18dB,-21dB
Power supply & Power Consumption	AC 120V or 220V;50-60Hz;<70W
Power of Amplifier	N.A.
The Dimension of External Power Supply	129x90x77mm
Product Dimension (WxDxH)	387.5x389.7x80.3mm
Net Weight	6kg
Shipping Dimension(WxDxH)	555x485x180mm/0.0485m3
Gross Weight	10.2kg

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice

HEINRICH

HEINRICH LIMITED, 69 Athlone Road London SW 22DU

W: www.heinrichlimited.com E: info@heinrichlimited.com