## **Economic Full Digital Conference Embedded Chairman Unit**



## **DESCRIPTION:**

Heinrich's H0336C is a cost-effective, fully digital conference embedded chairman unit that offers superior audio quality and advanced features. With a 48kHz sampling rate, it delivers sound clarity that surpasses CD standards. The built-in DSP audio processing eliminates low-frequency impact sounds, ensuring a clean and crisp listening experience. The touch button design eliminates the noise associated with traditional mechanical buttons, providing a neat and convenient user interface. The unit utilizes 100M network transmission for efficient hand-in-hand cascading, ensuring uninterrupted sound quality even over long distances. The voice control function intelligently activates the microphone when a speaker's voice is detected, offering customizable sensitivity and closing time settings. The internal feedback suppression effectively prevents squealing, while the 5-band EQ adjustment allows for fine-tuning sound effects to match different speakers' voice characteristics.

## **FEATURES**:

• The microphone adopts the sampling rate of 48kHz, which is higher than the CD sound quality, clear and bright sound, built-in DSP audio processing inside, without the low-frequency impact sound.

• Designed with touch buttons, no knocking noise during operation, neat and convenient. Use 100M network transmission to realize hand-in-hand cascade, long-distance transmission will not have any impact on sound quality.

• With voice control function, the microphone can be turned on intelligently. Support adjusting the voice control sensitivity and setting the closing time.

• Support internal feedback suppression function, effectively prevent squealing. Support 5-band EQ adjustment function, sound effects can be adjusted according to different speakers' voice characteristics to achieve the perfect effect.

- The chairman has a priority function and can turn off all delegate microphones that are speaking.
- Support the function of speech timekeeping and speech countdown.
- Support voting and rating functions; the chairman unit can initiate voting and sign-in; data statistics can be fulfilled without a PC.
- Support multiple language receiving channels: 63 + 1 (default).
- The microphone comes with a built-in 1W speaker.

HEINRICH

HEINRICH LIMITED, Marshall Avenue Worthing BN14 0ES W: www.heinrichlimited.com E: info@heinrichlimited.com

## **SPECIFICATIONS:**

HEINRICH

Model	H0336C
Microphone type	Cardioid Electret
Frequency response	80Hz~20KHz
Microphone input impedance	680Ω
Sensitivity	-41±1.5dB (OdB=1V/Pa,at 1KHz)
Maximum SPL	120dB
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>90dB
THD	<0.1%
MAX power consumption	2W
Headphone load	>16Ω
Headphone volume	Maximum 40mW
Headphone jack	3.5mm dual channel jack
Connection method	Network cable connection
Hand-in-hand expansion port	Support
Power supply	Powered by controller of DC36V
Color	Black
Voting function	Five key for election, three key for voting, five key for rating
Simultaneous interpretation	63+1 channels
Sign-in function	Touch button to sign in
Display	OLED full viewing angle low power display
Weight	0.55kg
Microphone pole	600mm
Size (L×W×H)	250x55x85mm
Installation method	Embedded installation
Cutout size	206x48mm

Disclaimer: As per our company policy one of the constant product improvements the right is there for reserved to modify the product specification without prior notice and the picture shown in the datasheet is a design base, the actual picture may vary.

HEINRICH LIMITED, Marshall Avenue Worthing BN14 OES W: www.heinrichlimited.com E: info@heinrichlimited.com