

IP- PTZ CAMERA

HC-IPP500



DESCRIPTION:

The HC-IPP500 5MP Outdoor PTZ Network Dome Camera from Heinrich features a 0.5" progressive scan CMOS sensor and 4.7-94mm varifocal lens to capture video at a maximum resolution of 2592 x 1944. The lens offers 40x optical zoom & digital zoom 16x for capturing detail at long distances.

The camera also features a wide range of smart functions such as intrusion detection, line crossing detection, audio exception, and motion detection. Enclosed in an IP67 rated housing, the system supports both on- and in-ceiling mounting options for environments in high-risk areas. The camera also supports smart functions and PTZ.

FEATURE:

- 0.5" progressive scan CMOS sensor.
- 2592 x 1944 resolution video at up to 30 fps.
- 4.7-94mm lens with 40x optical zoom & 16x digital zoom.
- DWDR (Digital Wide Dynamic Range).
- 3D intelligent positioning function.
- IP67 rated enclosure.
- 24 VAC / PoE power input.

IP- PTZ CAMERA

SPECIFICATION:

Model	HC-IPP500
Image sensor	0.5" CMOS sensor
Video Resolution	5 Megapixel
Frame rate	1~25f/s variable
Video Compression	H.265+/MJPEG/MPEG4, H.264 encoding with Baseline/Main/High profile
Video Streaming	Triple Stream
IR Range	Upto 200 metres
WDR	140dB
Security Measures	User name & Password
Shutter	1/30,000 seconds
Minimum Illumination	Color 0.05Lux@(F1.2,AGC ON), 0Lux with IR, Blank & White 0.001Lux@(F1.2,AGC ON), 0Lux with IR
Noise-signal Ratio	>70dB
Day and Night Function	Auto (ICR) / Color / B&W
Compression	H.264/M-JPEG
Streaming	Dual
Resolution	2592 X 1944
Auto-Iris	Yes
Frame Rate	Max 1080P @ 30fps
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC/HLC
White Balance	Auto/Natural/Manual
Gain Control	Auto/Natural
Noise Reduction	3D DNR
Motion Detection	ON/OFF
Web Viewer	Mozilla Firefox: 7 or above (streaming only), Chrome: 17 or above (streaming only) Internet Explorer 7.x, 8.x, 9.x, 10, 11
Image Setting	Saturation, brightness, sharpness, contrast, sharpeness adjustable through client software or web browser
On Screen Display	Yes (optional)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP,
ONVIF Support	Yes
Communication Interface	1 RJ45 10M / 100M ethernet port
Smart IR	Yes
Noise Reduction	2D / 3D
Power Supply	DC12V±10%
Mount Option	Long arm wall mount
External I/O Terminals	1 x alarm in / 1 x alarm Out
Event Trigger	Manual, Automatic (motion detection, alarm, schedule, cycle)
Event Notification	FTP, Email, SD Card
SD Card Support	256 GB
Material of housing con.	Aluminium

IP- PTZ CAMERA

Operation temp.	-10° to +60°
Lens Type	Motorized varifocal
Type of Camera Housing	Dome type
Tilt Speed	Any Value
Tilt Range Below Hori.	0° to 90°
Tilt Range Above Hori.	0° to 15°
Onvif Support	S,G,Q,T Profile
Certification	BIS, CE, ROHS, FCC