

30W Coaxial Ceiling Loudspeaker

HDS30-T



FEATURE:

- Built-in 100v/70v transformer
- In-ceiling type loudspeaker
- 5" +1.5" coaxial speaker unit
- Power output RMS 30W @100V
- Built-in crossover for hi-fi level use
- Metal grille, ABS baffle & ABS back cover
- Paint in white color
- Secure flush mount installation

DESCRIPTION

The Heinrich HDS30-T 30W. HEINRICH all speakers support EASE, CATT, ULYSSES models for acoustic studies. This means the acoustic model can be designed to simulate the sound quality and distribution prior to installation All HEINRICH loudspeaker have undergone trogh testing procedure to ensure that all products compliance with LOW VOLTAGE DIRECTIVE (BS EN 60065, 2003) and EMC (BS EN 61000-6-Part 1/2/3/4).

The HDS30-T is a ceiling speaker built-in 70v/100v transformer. The 70v/100v transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers. The built-in 5"+1.5" coaxial speaker driver is designed of wide frequency response 90-20kHz, and rated power output is 30 watts. The metal grille, ABS baffle and ABS back cover are painted in attractive white color. Its flush mount type makes the easy and secure installation. It is ideal choice for industrial and commercial applications in hotel, school, shopping mall office and factory where background music and paging is needed.

SPECIFICATION:


Model	HDS30-T
Power Taps @ 100V	30W/15W
Power Taps @70V	15W/7.5W
Impedance	Black: com,Red: 330Ω
SPL(1W/1M)	90dB±3dB
Max. SPL (Rated W/1M)	105dB
Frequency Response (-10dB)	90-20KHz
Finish	Baffle : ABS, White Grille : Steel, White
Speaker Driver	5" x 1 1.5" x 1
Cutout Size	210mm
Dimensions	240x 155mm
Weight	2Kg
Mounting	Flush mount dog ears

30W Coaxial Ceiling Loudspeaker


Appearance:



Direction Diagram:



Frequency Response:



As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice