

IP Network Outdoor Intercom Station IP-INT100

IP-INT100



FEATURE:

- ✓ Ideal solution for outdoor or indoor two-way communication system in noisy, dusty, high temp and acid or alkaline environment.
- ✓ IP network intercom system very suitable for big scale installation system whether by CAT5 cable or fibre optical cable.
- ✓ Aluminium finish with damage proof screw fixing up.
- ✓ Aluminium finish with damage proof screw fixing up.
- ✓ Both surface or embedded mounting ways with supplied mounting box.
- ✓ Classic range high quality IP intercom panel.
- ✓ Intercom panel built-in speaker and microphone.
- ✓ Full duplex two-way communication system.
- ✓ It can start the communication to the call station by pressing the call button, the call station will be reminded with ring call and indicator as which intercom panel from where is calling. The call will be automatically transferred to next call station once busy, no answer or fault occurred.
- ✓ With one contact output and contact input for third party communication.
- ✓ Non-dedicated network is needed, the system could be easily built-up over existing LAN/WAN network.
- ✓ Embedded server Linux technology with two ARM and DSP high speed chip.
- ✓ Max support 64,000 call stations working at the same time.
- ✓ Start time less than 0.1 second, and network data delay of less than 100 milliseconds.
- ✓ Waterproof rate of IP66.
- ✓ It is powered by DC12V, the power adapter is included.



As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice

IP Network Outdoor Intercom Station IP-INT100

SPECIFICATION:

Model	IP-INT100
Mounting	Standard RJ45 port
Power Supply	Support both surface or embedded by supplied mounting box
Power Consumption	DC 12V
Network Protocol	5W
Network Speed	TCP, UDP, ARP, ICMP, IGMP
Audio Sampling	10/100 Mbps
Transmission Rate	8KHz-44.1KHz,16 bits
S/N Ratio	Kbps to 320Kbps
Frequency Response	≥ 90dB
Data Delay	20Hz-20hz
Waterproof Rate	100 Milliseconds
Connector	One line output & one RJ45 port for LAN, one contact input and one contact output
Dimensions	255 x 115 x 50 (W x D X H)mm



As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice