UHF Wireless Conference System Chairman Unit UHF Wireless Conference System Delegate Unit





DC1UHF



FEATURE:

- $\sqrt{\text{Using engineering plastics materials with novel appearance design, built-in antenna.}}$
- $\sqrt{}$ Unique new anti-noise single directional high sensitive capacitance pickup, provide perfect conference voice.
- √ Large-screen LCD display; hierarchical menu design; simple and convenient operation; it can display the signal strength,battery power; battery under-voltage warning control, frequency channel, channel number and other information.
- $\sqrt{\text{Ultra-low power consumption, more than 8 hours of continuous speech time and more than 20 hours of standby time.}$
- $\sqrt{}$ Audio channel and control channel are all transmitted by wireless way, no need other cables, signal coverage can be moved conveniently and flexible.
- √ Delegate units with speech key, mute/menu Setting keys and volume plus or minus buttons, chairman priority key,
- $\sqrt{}$ totally four different types of keys.
- $\sqrt{}$ Delegate units with pickup lamp, which can display unit statement.
- $\sqrt{}$ Chairman unit has priority access functions to cut of the delegate unit speech.

SPECIFICATION:

Model	MC1UHF / DC1UHF
Audio channel	
Communication mode	UHF Wireless (one way)
Number of channel	5 channel, one for chairman , four channels for delegates
Frequency range	500MHz-950MHz
Modulation system	FM
Infrared radiation power	+10dBM
Maximum modulation	60K
Radiant power	≤+9dBm
Microphone sensitivity	-44dB±2dB
Frequency deviation	<0.002
SNR	>85dB
THD	≤0.8%
Frequency response	50Hz-15KHz
Pick-up range	10-30cm
Control channel	
Communication mode	wireless
Number of channel	16
Frequency range	422.4MHz-438.4MHz
Modulation mode	FSK

Comptable conference host unit CE0590MH

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice

